



# PRESTONE COMMAND® TECHNOLOGY COMPATIBILITY

## HEAVY DUTY ANTIFREEZE + COOLANT REFERENCE CHART



Product Name	Color	Extended Service Interval	Nitrited ELC 750K Miles*	Nitrite Free ELC 750K Miles*	Nitrite Free Non-2EH ELC w/Cor-Guard® 1M Miles*
Peak Final Charge Pro-Series	RED				✓
Peak Final Charge Global	RED			✓	✓
Valvoline Zerex ELC NF	YELLOW			✓	✓
Shell Rotella ELC - NF	RED			✓	✓
Cummins Fleetguard ES Compleat OAT	RED			✓	✓
Chevron Delo - NF	PINK			✓	✓
Mack XLC	PINK			✓	✓
Alliance Truck Parts Nitrite Free	RED			✓	✓
Castrol Heavy Duty Extended Life	RED			✓	✓
Detroit Diesel Power Cool Plus	RED			✓	✓
John Deere Cool-Guard II	GOLD			✓	✓
Chevron Delo XLC	RED			✓	✓
Volvo Penta VCS	YELLOW			✓	✓
Volvo Extended Life NF	RED			✓	✓
Mobil Delvac ELC	RED			✓	✓
Komatsu Super Coolant AF-NAC	BLUE			✓	✓

Nitrited Organic Acid (NOAT)	Color	Nitrited ELC 750K Miles*	Nitrite Free ELC 750K Miles*	Nitrite Free Non-2EH ELC w/Cor-Guard® 1M Miles*
Texaco ELC	RED		✓	
Peak Final Charge NOAT	RED		✓	
Castrol Heavy Duty Extended Life	RED		✓	
Alliance Truck Parts Extended Life OAT	RED		✓	
Cummins Fleetguard ES Compleat NOAT	RED		✓	
Paccar TRP ELC	RED		✓	
Shell Rotella ELC	RED		✓	
CAT Extended Life	RED		✓	
Valvoline Zerex Extended Life	RED		✓	
Chevron Delo ELC	RED		✓	
John Deere Cool-Guard	GREEN		✓	

Fully Formulated SCA Pre-Charged (ESI)	Color	Nitrited ELC 750K Miles*	Nitrite Free ELC 750K Miles*	Nitrite Free Non-2EH ELC w/Cor-Guard® 1M Miles*
Valvoline G05	GOLD	✓		
Texaco HD Coolant	PURPLE	✓		
Peak Fleet Charge	PINK	✓		
Cummins Fleetguard Fleetcool EX	PINK	✓		
Cummins Fleetguard ES Compleat	BLUE	✓		
Alliance SCA Precharge	PINK	✓		
CAT DEAC	PINK	✓		
Detroit Diesel Power Cool	PINK	✓		
Paccar TRP Heavy Duty	PURPLE	✓		
Castrol Heavy Duty	PURPLE	✓		
Chevron Heavy Duty	PURPLE	✓		
Shell Rotella Fully Formulated	PURPLE	✓		
Mobil SCA Precharge	PINK	✓		
Valvoline Zerex Pre-Charged	GREEN	✓		
Cummins Fleetguard Fleetcool	GREEN	✓		
Valvoline Zerex Fully Formulated	PINK	✓		



AFC13000

AFC13100

## Prestone Command® Heavy Duty Nitrite Free ELC with Cor-Guard® Antifreeze + Coolant

### ✓ Industry Leading Protection

Eliminates Engine Damaging Rust & Corrosion with Patented Cor-Guard® Technology

### ✓ 1,000,000 Mile Fluid Guarantee\*

For Use In: Vehicles Classes 1-8  
Compatibility: NF Non-2EH, NF-OAT

**Cummins® Certified**

CES 14603  
CES 14636  
CES 14439

\*Provides extended life protection which meets the vehicle manufacturer recommended change intervals for all DOT Truck Classes including up to 1,000,000 miles for Class 8 vehicles, when properly flushed, filled and maintained using only Heavy Duty Nitrite Free Coolant with Cor-Guard additive. Prestone.com or 1-888-269-0750 for all guarantee requirements and limitations. Class 8 wet sleeve liner applications. With a complete flush/drain and fill per manufacturer's recommendations. Always refer to the vehicle manufacturer owner's or service manual for the recommended change intervals, cooling system capacity, and specific cooling system service instructions.

CONCENTRATE	UPC	50/50	UPC	PACK
AFC13000	7 97496-88112 0	AFC13100	7 97496-88114 4	6/1 gal.
AFC13000-55	7 97496-88126 7	AFC13100-55	7 97496-88128 1	55 gal. drum
AFC13000-1KL	7 97496-88127 4	AFC13100-1KL	7 97496-88129 8	264 gal. tote



AFC12000

AFC12100

## Prestone Command® Heavy Duty Nitrite Free Extended Life Antifreeze + Coolant

### ✓ Protects Against Rust & Corrosion

### ✓ 750,000 Mile Fluid Guarantee\*

For Use In: Vehicles Classes 1-8  
Compatibility: NF-OAT

**Cummins® Certified - CES 14636  
CES 14439**

**Detroit Diesel® Certified - 93K217**

\*Fluid service life guaranteed up to earlier of 750,000 mi. or 15,000 hrs. Follow steps to achieve service life: (1) Perform cooling system flush, then fill cooling system with proper mixture of PRESTONE COMMAND® Nitrite Free ELC Concentrate and high quality water. (2) Top off coolant levels as necessary using only PRESTONE COMMAND® Nitrite Free ELC Prediluted. (3) Test coolant every 6,000 hrs or 1 yr intervals using refractometer to test correct coolant/water mixture and using test strips to assess pH and nitrite level for any contamination. (4) Add PRESTONE COMMAND® Nitrite Free ELC Prediluted at 600,000 mi. and as necessary to maintain inhibitor level and pH. (5) Use new coolant if replacing a cooling system part. Guarantee may be subject to other terms and conditions – please visit Prestone.com or call 1-888-269-0750 for further information.

CONCENTRATE	UPC	50/50	UPC	PACK
AFC12000	7 97496-87906 6	AFC12100	7 97496-87910 3	6/1 gal.
AFC12000-55	7 97496-87908 0	AFC12100-55	7 97496-87912 7	55 gal. drum
AFC12000-1KL	7 97496-87909 7	AFC12100-1KL	7 97496-87913 4	264 gal. tote



AFC11000

AFC11100

## Prestone Command® Heavy Duty Nitrited Extended Life Antifreeze + Coolant

### ✓ Protects Against Rust & Corrosion

### ✓ 750,000 Mile Fluid Guarantee\*

When extender added at 300,000 & 600,000 miles

For Use In: Vehicles Classes 6-8  
Compatibility: NOAT

**CAT EC-1 Comparable**

**Cummins® Certified - CES 14439**

\*Fluid service life guaranteed up to earlier of 750,000 mi. or 15,000 hrs. Follow steps to achieve service life: (1) Perform cooling system flush, then fill cooling system with proper mixture of PRESTONE COMMAND® Nitrited ELC Concentrate and high quality water. (2) Top off coolant levels as necessary using only PRESTONE COMMAND® Nitrited ELC Prediluted. (3) Test coolant every 6,000 hrs or 1 yr intervals using refractometer to test correct coolant/water mixture and using test strips to assess nitrite level and pH. (4) Add PRESTONE COMMAND® Nitrited ELC Prediluted or a NOAT coolant extender in accordance with OEM recommendations at 300,000 mi and 600,000 mi and as necessary to maintain nitrite level and pH. (5) Use new coolant if replacing a cooling system part. Guarantee may be subject to other terms and conditions – please visit Prestone.com or call 1-888-269-0750 for further information.

CONCENTRATE	UPC	50/50	UPC	PACK
AFC11000	7 97496-87757 4	AFC11100	7 97496-87761 1	6/1 gal.
AFC11000-55	7 97496-87758 1	AFC11100-55	7 97496-87762 8	55 gal. drum
AFC11000-1KL	7 97496-87759 8	AFC11100-1KL	7 97496-87763 5	264 gal. tote



AFC10000

AFC10100

## Prestone Command® Heavy Duty Extended Service Interval Antifreeze + Coolant

### ✓ Protects Against Rust & Corrosion

### ✓ Low Silicate Formula

### ✓ No Phosphates

For Use In: Vehicles Classes 6-8  
Compatibility: ESI & IAT

**Detroit Diesel® Certified - 93K217**

CONCENTRATE	UPC	50/50	UPC	PACK
AFC10000	7 97496-87765 9	AFC10100	7 97496-87769 7	6/1 gal.
AFC10000-55	7 97496-87766 6	AFC10100-55	7 97496-87770 3	55 gal. drum
AFC10000-1KL	7 97496-87767 3	AFC10100-1KL	7 97496-87774 1	264 gal. tote